











see what Delta can do

## SHOWER FAUCET TRIM

Shower Trim with Two Function Diverter

## **STANDARD SPECIFICATIONS**

- Monitor® 14 Series pressure balanced single function bath mixing valve trim
- · Two function diverter
- Main control utilizes single-function pressure balanced cartridge
- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system
- For use with MultiChoice<sup>®</sup> Universal rough valve body (R22000 Series)
- · Back-to-back installation capability
- Field adjustable means to limit handle rotation into hot water zone
- Top handle controls diverter functions; bottom handle controls on/off and temperature
- Botton handle 120° maximum rotation
- All parts replaceable from the front of the valve
- Maximum system flow rate 5.0 gpm @ 60 psi with R22000
- Max. flow rate of showerhead and handshower 1.75 gpm @ 80 psi, 6.6 L/min @ 552 kPa
- Cartridges included

## WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, 1 year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.



## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASSE 1016 / ASME A112.1016 / CSA B125.16 Landicates ADA compliance to
- ICC/ANSI A117.1 Valve control only
- EPA WaterSense®

**Delta Faucet Company** 

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2023 Delta Faucet Company