

Single Receptacle Power Cord Reels

Model with cord & bumper	Cord Ending	Cord Specifications					Volts		Shipping Weight	Size Index
		AWG	mm ²	# Cond	ft	m	Type*	Amps		
L 4035 163 3	Single receptacle NEMA 5-15R, Inlet straight blade plug NEMA 5-15P	16	1.33	3	35	11	SJTOW	125	13	25 11 1
L 4050 163 3		16	1.33	3	50	15	SJTOW	125	13	26 12 1
L 4545 123 3		12	3.32	3	45	14	SJEOOW	125	15	27 12 1
L 5550 123 3		12	3.32	3	50	15	SJEOOW	125	15	44 20 3
L 70075 123 3		12	3.32	3	75	23	SE0OW	125	15	70 32 5
L 70100 123 3		12	3.32	3	100	30	SE0OW	125	15	74 34 5
L 4525 123 3A	Single receptacle NEMA 5-20R, Inlet straight blade plug NEMA 5-20P	12	3.32	3	25	8	SJEOOW	125	20	25 11 1
L 4545 123 3A		12	3.32	3	45	14	SJEOOW	125	20	28 13 1
L 5550 123 3A		12	3.32	3	50	15	SJEOOW	125	20	44 20 3
L 70075 123 3A		12	3.32	3	75	23	SE0OW	125	20	70 32 5
L 70100 123 3A		12	3.32	3	100	30	SE0OW	125	20	74 34 5
L 4545 123 3AC		12	3.32	3	45	14	SJEOOW	125	20	28 13 1
L 70075 123 3AC	Single receptacle NEMA 5-20R, Inlet twist lock plug NEMA L5-20P	12	3.32	3	75	23	SE0OW	125	20	70 32 5
L 70075 123 15BC	Twist lock single receptacle NEMA L5-15R, Inlet twist lock plug NEMA L5-15P	12	3.32	3	75	23	SE0OW	125	15	70 32 5
L 4545 123 3B	Twist lock single receptacle NEMA L5-20R, Inlet straight blade plug NEMA 5-20P	12	3.32	3	45	14	SJEOOW	125	20	28 13 1
L 5550 123 3B		12	3.32	3	50	15	SJEOOW	125	20	44 20 3
L 70100 123 3B		12	3.32	3	100	30	SE0OW	125	20	74 34 5

For indoor non-weathertight applications only. All models UL listed at 125 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 43. *Cord type designation shows all combinations of cord types that may be used, only UL approved cord types will be used.



L 5550 123 3A



Cord End Specifications

		#3 - Single Receptacle Single 15 AMP with clamp type strain relief for 16 and 12 AWG cord. NEMA 5-15R
		#3A/3AC - Single Receptacle Single 20 AMP. NEMA 5-20R
		#15BC - Twist Lock Receptacle Single 15 AMP with twist lock connector. NEMA L5-15R
		#3B - Twist Lock Receptacle Single 20 AMP with twist lock connector. NEMA L5-20R

Many more cord reel models available in addition to the charts on pages 29-32. Contact Reelcraft for more information. *Minimum order quantities may apply



Flying Lead and Bare Power Cord Reels

Model	Cord Ending	Cord Specifications					Volts/ Amps	Volts/ Amps	Shipping Weight*	Size Index
		AWG	mm ²	# Cond	ft	m	Type**			
L 4050 163 X	Flying lead	16	1.33	3	50	15	SJEOOW	125 / 13	220 / 6.5	26 12 1
L 4545 123 X		12	3.32	3	45	14	SJEOOW	125 / 20	220 / 10	25 11 1
L 5550 123 X		12	3.32	3	50	15	SJEOOW	125 / 20	220 / 10	35 16 3
L 70075 123 X		12	3.32	3	75	23	SE0OW	125 / 20	220 / 10	69 31 6
L 70100 123 X		12	3.32	3	100	30	SE0OW	125 / 20	220 / 10	73 33 6
L 5550 124 X		12	3.32	4	50	15	SE0OW	-----	600 / 16	43 20 3
L 70100 124 X		12	3.32	4	100	30	SE0OW	-----	600 / 16	75 34 6
L 5750 103 X		10	5.27	3	50	15	SE0OW	125 / 30	220 / 15	55 25 4
L 7050 104 X		10	5.27	4	50	15	SE0OW	-----	600 / 20	65 29 7
L 4500	Bare reel	12	3.32	3	45	14	SJEOOW	125 / 20	220 / 10	21 10 1
L 70100		12	3.32	3	100	30	SE0OW	125 / 20	220 / 10	58 26 6
L 5000		10	5.27	3	35	11	SO	125 / 30	220 / 15	29 13 2
L 5700		10	5.27	3	50	15	SE0OW	125 / 30	220 / 15	37 17 4
L 7000		6	13.3	4	35	11	SOOW	-----	220 / 45	41 19 7

For indoor non-weathertight applications only. All models UL listed at 125/220 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 43. Flying lead models include cord and bumper. **Equivalent cord type may be used.



L 70100 123 X



Cord End Specifications

		X - Flying Lead Flying leads on inlet and outlet and conduit box.
--	--	---

Refer to page 32 for dimensional drawings for all cord reels.