

NEMA 4 Power Cord Reels

- NEMA 4 rating provides protection against water or dust, indoor and out
- Cast aluminum construction with yellow powder coat finish
- Large, easy to access junction box
- One inch (NPT) pipe thread opening provided for conduit inlet
- Guide arm is adjustable every 5° over a 270° arc
- Containerized drive spring allows for safer, easier maintenance



**Interactive
Reel Catalog**

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



L NM440 103 X

| Model with cord & bumper | Cord Ending | Cord Specifications | | | | | | Volts | Amps | Shipping Weight | |
|--------------------------|-------------|---------------------|-----------------|---------|----|----|------|-------|------|-----------------|----|
| | | AWG | mm ² | # Cond. | ft | m | Type | | | lbs | kg |
| L NM450 163 X | Flying Lead | 16 | 1.31 | 3 | 50 | 15 | SOW | 600 | 9 | 43 | 20 |
| L NM450 143 X | | 14 | 2.08 | 3 | 50 | 15 | SOW | 600 | 13 | 48 | 22 |
| L NM445 144 X | | 14 | 2.08 | 4 | 45 | 14 | SOW | 600 | 11 | 50 | 23 |
| L NM425 123 X | | 12 | 3.31 | 3 | 25 | 8 | SOW | 600 | 18 | 44 | 20 |
| L NM450 123 X | | 12 | 3.31 | 3 | 50 | 15 | SOW | 600 | 18 | 50 | 23 |
| L NM440 124 X | | 12 | 3.31 | 4 | 40 | 12 | SOW | 600 | 14 | 50 | 23 |
| L NM440 103 X | | 10 | 5.26 | 3 | 40 | 12 | SOW | 600 | 22 | 50 | 23 |
| L NM430 104 X | | 10 | 5.26 | 4 | 30 | 9 | SOW | 600 | 16 | 50 | 23 |

All models UL listed at 125 Volt 60 HZ single phase. One inch (NPT) pipe thread opening provided for conduit inlet.

| Dimensions | | | | | | |
|------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|-------------------------------|-------------------------------|
| | A | B | C | D | E | F |
| in | 14 ¹ / ₂ | 13 ¹ / ₂ | 4 ⁷ / ₁₆ | 3 ¹ / ₁₆ | 9 ⁵ / ₈ | 7 ¹ / ₄ |
| mm | 368 | 343 | 113 | 78 | 244 | 184 |

Stainless Steel Power Cord Reels

- Designed for applications where corrosion or sanitation are a concern
- Includes a robotically welded base, engineered structural supports, and heavy gauge, electropolished 304L stainless steel
- Robust collector ring assures maximum conductivity current flow
- Includes a 4-5 ft. pigtail and a multi-positional guide arm
- Space-saving design makes them ideal for minimum space requirements



**Interactive
Reel Catalog**

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



LS 5445 123 3A

| Model with Cord | Cord Ending | Cord Specifications | | | | | | Volts | Amps | Shipping Weight | |
|-----------------|----------------------|---------------------|-----------------|---------|----|----|--------|-------|------|-----------------|----|
| | | AWG | mm ² | # Cond. | ft | m | Type | | | lbs | kg |
| LS 5445 123 3 | Single Receptacle | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 15 | 31 | 14 |
| LS 5445 123 7A* | Duplex Box w/GFCI(F) | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 20 | 33 | 15 |
| LS 5445 123 9G* | Triple Tap w/GFCI(F) | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 15 | 33 | 15 |

For indoor non-weathertight applications only, in non-hazardous areas. *The GFCI Receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 43.

| Dimensions | | | | | | |
|------------|--------------------------------|--------------------------------|-------------------------------|-------------------------------|--------------------------------|-------------------------------|
| | A | B | C | D | E | F |
| in | 14 ³ / ₈ | 14 ¹ / ₄ | 9 ³ / ₄ | 2 ¹ / ₂ | 10 ¹ / ₂ | 2 ¹ / ₈ |
| mm | 365 | 362 | 248 | 64 | 267 | 54 |